## XEROX® PRIMELINK® PRINTER

# The world's #1\* entry production color printer just got even better.



C9065 AND C9070



## Xerox<sup>®</sup> PrimeLink<sup>®</sup> C9065 and C9070 Printer

The Xerox<sup>®</sup> PrimeLink<sup>®</sup> C9065/C9070 delivers the most adaptable capabilities on the market. From superior image quality and unmatched media flexibility to professional-grade finishing, automation and security, it takes entry level to the next level.



#### IMPROVE YOUR IMAGE

Entry-level price point shouldn't mean entrylevel image quality. With PrimeLink, you can deliver stunning output on every job, every time.

It all starts with resolution. 2400 x 2400 dpi means you get outstanding fine-line detail and text with vivid images and smooth color transitions — even at speeds of up to 70 ppm. EFI servers with embedded PANTONE® technologies such as PANTONE® GOE and PANTONE® PLUS ensure the colors you want are the colors you get.

And a combination of Xerox® Emulsion Aggregation (EA) toner with ultra-low melt technology, +/- 1.5 mm front-to-back registration and Simple Image Quality Adjustment (SIQA) means you get consistent quality from your first print to your last.



<sup>\*</sup> Idealliance, Fogra, and Adobe PDF Print Engine achieved with the optional EFI server

#### WORK SMARTER, NOT HARDER

Looming deadlines are the norm. Now, there's no reason to compromise. Adding a PrimeLink to your arsenal lets you upgrade your productivity in ways you wouldn't think possible.

Designed to promote multitasking and collaboration, it's customizable to suit your work style. The Xerox<sup>®</sup> Integrated Color Server comes standard. Or you can choose from one of three optional EFI servers for more capabilities and more volume. All you have to do is select the best fit based on your business applications and the level of automation and color accuracy you need.

The printer also has access to the Xerox App Gallery. With apps that connect to leading applications including Box®, Microsoft® OneDrive®, Google Drive™, Dropbox™ and Microsoft Office 365™, you can print and scan directly to and from the cloud, simplify workflows and automate complex tasks.

Plus, built-in mobile connectivity with @PrintByXerox lets your team stay on-task when they're on the go. With this feature, PrimeLink can securely accept print submissions from any email-enabled device — no extra software required.

It's all there with the touch of a button. Say yes to more, and Xerox<sup>®</sup> PrimeLink C9065/C9070 will help you deliver.

#### SERVE AND PROTECT

PrimeLink applies a strategic approach to security to keep your network and projects safe from prying eyes. Stop suspicious activity where it starts with our comprehensive approach to security:

- Multiple layers of security include data encryption, access controls, disk overwrite and industry certifications.
- Audit Log ensures an audit trail of operators' key events. These logs are imperative for Administrators/Key Operators to use for troubleshooting, resource optimization and security audits.
- Secure Print holds documents for release until you're ready to retrieve them.
- Secure Scanning includes password protection for PDFs and folders, as well as encryption for scanning to email.

#### FINISH STRONG

PrimeLink delivers media latitude and finishing options that are best-in-class and unparalleled in an entry-level device.

Print on specialty stocks and heavyweight stocks up to 350 gsm. Print up to 26" (660 mm) with the Extra Long Sheet (XLS) capability up to 220 gsm. And print long runs without refilling the paper tray using high volume feeding options.

Finishing options are professional-grade, easy to navigate and nearly endless. Enjoy options ranging from full-bleed trimmed booklets to punch, crease and fold.



#### Xerox<sup>®</sup> PrimeLink<sup>®</sup> C9065/C9070 Printer

- **1 Two-Tray Oversized High Capacity Feeder:** Adds 4,000 sheets in sizes from 4 x 6 in. /100 x 148 mm to 13 x 19.2 in./330 x 488 mm (up to 350 gsm). Up to 13 x 26 in./330 x 660mm via Tray 5 (up to 220 gsm).
- 2 Extra Long Sheet (XLS) Capability: Print banners, book jackets, calendars and other applications up to 26 in. (660 mm) long, and up to 220 gsm via Tray 5 (Bypass).
- **3 Control Panel**: An intuitive user interface makes it simple to access general print, copy, scan and fax functions, integrated color server, useful apps from the Xerox App Gallery, color controls, security features and much more.
- **4 Integrated Scanner:** Single Pass Duplex Automatic Document Feeder scans up to 270 impressions per minute; 600 dots per inch color up to 11 x 17/A3. Scan to a variety of output options; desktop, USB, mailbox, FTP, SFTP, SMB and Job Flow multi-destination scanning.
- 5 Xerox<sup>®</sup> PrimeLink C9065/C9070 Printer: Prints, copies, scans and faxes all while delivering stunning color image quality at a highly productive 65 ppm color and 70 ppm black-and-white (C9065) or 70 ppm color and 75 ppm black-and-white (C9070).
- 6 Five Internal Trays (Standard): Includes a 12 x 18 in./SRA3 tray and Tray 5 (Bypass) max weight up to 350 gsm and up to 26 in./ 660 mm sheet size.
- 7 Xerox® Interface Decurler Module: Inline paper cooling and decurler unit improves throughput and efficiency, connecting Production Ready finishing modules, ensuring flat sheets for reliability and speed.

- **8 Xerox Inserter:** Insert preprinted or blank media into printed documents with a tray capacity of 250 sheets, sheet sizes up to 13 x 19.2 in. (330 x 488 mm) and 350 gsm.
- 9 GBC<sup>®</sup> AdvancedPunch Pro<sup>™</sup>: Lets you create bound documents in-house by combining printing, punching and collating into one convenient step. Choose the punch to fit your needs.
- **10 Xerox® Crease and Two-sided Trimmer:** Trims 6-25 mm from the head and foot of prints or booklets to produce an even edge and creases spine. Available with Production Ready Finishers.
- **11 Xerox® C/Z Folder:** Produces Z-fold, C-Fold and Engineering Z-Fold.
- 12 Xerox<sup>®</sup> Production Ready Finisher Booklet Maker: Ensures consistent high-quality stapled sets for small or large documents with a variable-length stapler, single or dual stapling option and a 100 sheet capacity. Plus, creates stapled booklets up to 30 sheets or 120 imposed pages (uncoated), or 15 sheets or 60 imposed pages (coated).
- **13 Xerox® SquareFold® Trimmer Module:** Enhances the power of the Production Ready Finisher with square fold of cover sheets and face trimming to produce booklets.

#### ADDITIONAL FEEDING AND FINISHING OPTIONS NOT PICTURED

- One-Tray Xerox® High Capacity Feeder Holds 2,000 sheets of 8.5 x 11 in. (A4) paper, 64–220 gsm.
- Banner Feed Guide An option for the Tray 5 (Bypass)/MSI/OHCF that increases reliability when feeding XLS or 350 gsm media.
- One-Tray Oversized High Capacity Feeder with Storage Cabinet — Adds 2,000 sheets in sizes from 4 x 6 in. / 100 x 148 mm to 13 x 19.2 in. / 330 x 488 mm (up to 350 gsm). Up to 13 x 26 in./330 x 660 mm via Tray 5 (up to 220 gsm).
- Offset Catch Tray 500-sheet stacking.
- Xerox<sup>®</sup> Business Ready Finisher A lighterduty option for finishing and stacking and staples up to 50 sheets uncoated/15 coated.
- Xerox<sup>®</sup> Business Ready Booklet Maker Finisher — Provides booklet making capability.
- Xerox<sup>®</sup> Production Ready Finisher Produces superior quality finishing and stacking with a 500-sheet top tray and 3,000-sheet stacker tray and built-in bi-directional decurler.
- Xerox<sup>®</sup> Production Ready Finisher Plus Provides same function as the Production Ready Finisher. Used to connect third-party inline finishing options.
- Xerox<sup>®</sup> Basic Punch An option for punching 2/3, 2/4 and Swedish 4-hole on the Production Ready Finisher and Booklet Maker.
- Plockmatic Pro 50/35 Booklet Maker Highest quality production booklets up to 200 pages (up to 50 sheets). Face trimming, square fold, rotate crease and bleed trim.
- Convenience Stapler Staples up to 50 sheets of 20 lb./80 gsm media.

FINISHING APPL	ICATIONS				
Sort and Collate	XLS	Tri-Fold	Square Fold	Face Trim	Hole Punch
Booklet	Tabloid Z-Fold	Z-Fold	2-Sided Trim	Basic Punch	Staple

### Xerox<sup>®</sup> PrimeLink<sup>®</sup> C9065 and C9070 Printer

	PRIMELINK C9065	Black and white	PRIMELINK C9070	Black and white			
	Color	Black-and-white	Color	Black-and-white			
	Up to 65 ppm	Up to 70 ppm	Up to 70 ppm	Up to 75 ppm			
I1 x 17 in. / A3	Up to 33 ppm	Up to 35 ppm	Up to 35 ppm	Up to 37 ppm			
2 x 18 in. / SRA3	Up to 29 ppm	Up to 30 ppm	Up to 30 ppm	Up to 33 ppm			
	Color	Black-and-white	Color	Black-and-white			
3.5 x 11 in. / A4	Up to 65 ppm 2-sided	Up to 70 ppm 2-sided	Up to 70 ppm 2-sided	Up to 75 ppm 2-sided			
14 47: (4)	32 sheets per minute	35 sheets per minute	35 sheets per minute	37 sheets per minute			
11 x 17 in. / A3	Up to 32 ppm 2-sided	Up to 35 ppm 2-sided 17 sheets per minute	Up to 35 ppm 2-sided	Up to 37 ppm 2-sided			
	16 sheets per minute	17 sheets per minute	18 sheets per minute				
Printer Dimensions	Height: 54.8 in. / 1,391.5 mm; Width: 62 in						
Monthly Duty Cycle	Up to 300,000 pages (maximum volume c	apacity expected in any one month, not exp	ected to be sustained on a regular basis)				
Average Monthly Print Volume (AMPV)	10,000 to 60,000 pages per month						
2aper Flexibility/Weights	Max Paper Capacity: 7,260 sheets (Tray 1	& 2: 500 sheets, Tray 3: 870 sheets, Tray 4:	ay 4: 1,140 sheets, Tray 5 (Bypass): 250 shea 1,140 sheets, Oversized High Capacity Tray 5 to A3; Tray 3: 7.25 x 10.5 in., 8.5 x 11 in. / B	1 & 2: 4,000 sheets)			
Image Quality Print Technology	Benchmark image quality with 2400 x 2400 dpi resolution with VCSEL ROS and EA Eco with ultra-low melt technology toner for a smooth, offset-like finish						
Line Screens	150/200/300/600 dot screen, 200 line screen, stochastic and enhanced text and graphics						
Registration	Advanced registration technology for tighter control						
Registration	Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity (available on all configurations)     +/- 1.5 mm. Variation will occur based on paper size, tray, etc.,						
Print Features	<ul> <li>Print, copy, fax and scan, including</li> </ul>		• XLS sheet size (Tray 5 and OHCF via	Tray 5) supporting up to 220gsm			
	Scan to PC, USB or Email, and mobile printing		<ul> <li>Up to 350 gsm (Tray 5 and OHCF only).</li> </ul>				
	Expansive media range lets you print everything from		auto-duplex up to 256 gsm (Bypass Tray and OHCF)				
	postcards to posters, both coated and uncoated stock, up to 350 gsm		<ul> <li>Xerox<sup>®</sup> replaceable units for toners, drums, fuser,</li> </ul>				
	<ul> <li>Xerox Extensible Interface Platform<sup>®</sup> (EIP) allows you to</li> </ul>		charge corotron, waste bottle, staples				
	connect to third-party software solutions		Custom Paper Setup and Paper Catalog				
	<ul> <li>Inline finishing options offer a professional polish with banner printing, stapling, hole-punching, folding and booklet</li> </ul>		Load-while-run toner and paper capability				
	making for presentations, brochures, reports and newsletters		Optional Features: Common Access Card Enablement				
	Kit, Accounting Options, Foreign Device Interface						
	Be secure with integrated security features such as     IP filtering, image overwrite, secure print, encrypted						
	IP filtering, image overwrite, secure print, encrypted Scan to Email, authentication and IPv6 support						
Servers	• Xerox <sup>®</sup> Integrated Color Server		Optional <ul> <li>Xerox® EX-c C9065/C9070 Print Serve</li> <li>Xerox® EX-i C9065/C9070 Print Serve</li> <li>Xerox® EX-i C9065/C9070 Print Serve</li> </ul>	er Powered by Fiery®			
Testa menta d Canana an	Kerox® EX C9065/C9070 Print Server Powered by Fiery®						
Integrated Scanner	Single-pass Duplex Automatic Document Feeder     Color or black and white scapper		Up to 270 ipm (color, up to 200 gsm)				
	<ul> <li>Color or black-and-white scanner</li> <li>Scan to text searchable PDF, PDF/A, thumbnail preview, XPS<sup>®</sup>, PCL<sup>®</sup> 6, HP-GL2</li> </ul>		<ul> <li>Up to 270 ipm (black-and-white, up to 200 gsm)</li> <li>Originals up to 11 x 17 in. (A3) in weights from 38 gsm</li> </ul>				
	<ul> <li>Scan to text searchable PDF, PDF/A, th (direct submission), TIFF, JPEG</li> </ul>	numbhall preview, XPS <sup>-</sup> , PCL <sup>-</sup> 6, HP-GL2	(16 lb. bond) to 200 gsm (53 lb. bond)				
	<ul> <li>250-sheet capacity</li> </ul>		(10 lb. bolid) to 200 gsill (33 lb. bolid	1)			
Optional Feeding	Optional High Capacity Feeder (HCF): 2,000 sheets; 7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4);						
optional ceanig	<b>Optional High Capacity Feeder (HCF):</b> 2,000 sneets; 7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4); 16 lb. bond to 60 lb. cover / 64 to 220 qsm (uncoated and coated)						
	Optional Oversized High Capacity Feeder (OHCF): One-Tray OHCF: 2,000 sheets plus Storage Cabinet; Tray 6: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in. / 330 x 488 mm (up to 350						
	Optional Oversized High Capacity Feede	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (up to 220 gsm).					
			561age easinet, may 6.5.5 x 5.6 min 100 x 1.6				
	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (L	up to 220 gsm).	330 x 488 mm (up to 350 qsm) Tray 5: Up to 13				
	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (u Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./	330 x 488 mm (up to 350 gsm) Tray 5: Up to 13	x 26 in./330 x 660 mm (up to 220 gsm).			
	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (L Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar <b>Business Ready Finisher: Offsetting Top</b>	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ • <b>Tray:</b> 500-sheets 8.5 x 11 in. / A4 unstaplec		x 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stapl			
	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar <b>Business Ready Finisher: Offsetting Top</b> 11x17 in., 8.5 x 14 in., A3 or 200 sets (single	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ T <b>ray:</b> 500-sheets 8.5 x 11 in. / A4 unstapled - position staple) 8.5 x 11 in. / A4. <b>Sizes:</b> Stad	330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 1. <b>Stacking Stapling Tray:</b> 3,000 sheets uns	x 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stapl apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to A			
	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar <b>Business Ready Finisher: Offsetting Top</b> 11x17 in., 8.5 x 14 in., A3 or 200 sets (single	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ • <b>Tray:</b> 500-sheets 8.5 x 11 in. / A4 unstapled • position staple) 8.5 x 11 in. / A4. <b>Sizes:</b> Stac punch and offset. <b>Paper weights:</b> Top Tray-	330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 I. <b>Stacking Stapling Tray:</b> 3,000 sheets uns :king; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St	x 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stapl apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to A			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ • Tray: 500-sheets 8.5 x 11 in. / A4 unstaplee • position staple) 8.5 x 11 in. / A4. <b>Sizes:</b> Stac punch and offset. <b>Paper weights:</b> Top Tray- ed and uncoated).	330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 I. <b>Stacking Stapling Tray:</b> 3,000 sheets uns :king; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St	ix 26 in./330 x 660 mm (up to 220 gsn). tapled or 100 sets (dual or 4-position stapl apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to A coated and uncoated). Stacker Tray-16 lb.			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ • Tray: 500-sheets 8.5 x 11 in. / A4 unstaplee • position staple) 8.5 x 11 in. / A4. <b>Sizes:</b> Stac punch and offset. <b>Paper weights:</b> Top Tray- ed and uncoated).	330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 1. <b>Stacking Stapling Tray</b> : 3,000 sheets uns sking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm ( 8.5 x 11 in. / A4 unstapled. <b>Stacking Stapling</b>	ix 26 in./330 x 660 mm (up to 220 gsn). tapled or 100 sets (dual or 4-position stapl apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to A coated and uncoated). Stacker Tray-16 lb.			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar <b>Business Ready Finisher: Offsetting Top</b> 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; r bond to 96 lb. cover / 60 to 256 gsm (coate <b>Business Ready Finisher Booklet Maker</b> (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in.	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in. / <b>Tray:</b> 500-sheets 8.5 x 11 in. / A4 unstapled - position staple) 8.5 x 11 in. / A4. <b>Sizes:</b> Stac punch and offset. <b>Paper weights:</b> Top Tray- ed and uncoated). <b>Finisher: Offsetting Top Tray:</b> 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2 / A4. <b>Sizes:</b> Stacking; 4 x 6 in. to 12 x 19.2 in. /	330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 1. <b>Stacking Stapling Tray</b> : 3,000 sheets uns king; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm ( 8.5 x 11 in. / A4 unstapled. <b>Stacking Stapling</b> 8/ SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17	ix 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stapl apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to A coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in./ B5 to A3.			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p	up to 220 gsm). nd 7: 39 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ <b>Tray:</b> 500-sheets 8.5 x 11 in. / A4 unstapled -position staple) 8.5 x 11 in. / A4. <b>Sizes:</b> Stac punch and offset. <b>Paper weights:</b> Top Tray- d and uncoated). <b>Finisher: Offsetting Top Tray:</b> 500-sheets 8 n staple) or 100 stapled sets of 11 x 17 in. / A2 / A4. <b>Sizes:</b> Stacking: 4 x 6 in. to 12 x 19.2 in. / unch and offset. <b>Paper weights:</b> Top Tray-16	330 x 488 mm (up to 350 gsm) Tray 5: Up to 12 4. <b>Stacking Stapling Tray</b> : 3,000 sheets uns kking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (r 8.5 x 11 in. / A4 unstapled. <b>Stacking Stapling</b> 8./ SRA3, 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3, Stapling; 7.25 x 10.5 in. to 11 x 17 lb. bond to 130 lb. cover / 60 to 350 gsm (coo	ix 26 in./330 x 660 mm (up to 220 gsn). tapled or 100 sets (dual or 4-position stapl apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to A coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. tted and uncoated),			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; r bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker I (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ tray: 500-sheets 8.5 x 11 in. / A4 unstaplee position staple) 8.5 x 11 in. / A4. Sizes: Stac punch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A3 / A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in./ unch and offset. Paper weights: Top Tray-16 to 256 gsm (coated and uncoated). Booklet M	330 x 488 mm (up to 350 gsm) Tray 5: Up to 12 1. <b>Stacking Stapling Tray</b> : 3,000 sheets uns- king; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (i 8.5 x 11 in. / A4 unstapled. <b>Stacking Stapling</b> 8/ SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 1b. bond to 130 lb. cover / 60 to 350 gsm (coc 4aker-16 lb. bond to 96 lb. cover / 60 to 256 gsm	ix 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to / coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ted and uncoated), im			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookl	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ <b>Tray:</b> 500-sheets 8.5 x 11 in. / A4 unstaplee e-position staple) 8.5 x 11 in. / A4. <b>Sizes:</b> Star punch and offset. <b>Paper weights:</b> Top Tray- d and uncoated). <b>Finisher: Offsetting Top Tray:</b> 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2 / A4. <b>Sizes:</b> Stackpaled sets of 11 x 17 in. / A2 unch and offset. <b>Paper weights:</b> Top Tray- to 256 gsm (coated and uncoated). Booklet M et Maker-Saddle-stirch 2 to 16 sheets (7 sheet	(330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 1. Stacking Stapling Tray: 3,000 sheets uns sking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm ( 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3/ SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 lb. bond to 130 lb. cover / 60 to 350 gsm (coc daker-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets at 17	ix 26 in/330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to / coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. tited and uncoated), m 7 to 220 gsm coated).			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in. , Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookl Production Ready Finisher (requires Inte	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstaplece -position staple) 8.5 x 11 in. / A4. Sizes: Stace upuch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2 / A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100	(330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 (1330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 (1350 gsm) Tray 5: Up to 13 (140 gsm) Tray 5: Up to 12 x 19.2 in. / A6 to SRA3, St (16 lb, bond to 130 lb, cover / 60 to 350 gsm ( (15 gsm), 11 x 17 in., 8.5 x 14 in., A3 or A6 to SRA3, Stapling; 7.25 x 10.5 in. to 11 x 17 (1b, bond to 130 lb, cover / 60 to 350 gsm (coc (aker-16 lb, bond to 96 lb, cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets at 17 sheets (90 gsm) uncoated, 35 sheets (90 gsm)	ix 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in./ B5 to coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in./ B5 to A3. tted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; r bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookl Production Ready Finisher (requires Inte 146mm to 11.7 x 17'/297 x 432mm. Max W	up to 220 gsm). nd 7:39 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstapled position staple) 8.5 x 11 in. / A4 unstapled position staple) 8.5 x 11 in. / A4. Sizes: Stac punch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 / A4. Sizes: Stacking: 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 /eight: 350 gsm. Options: Punch, Inserter an	(330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 1. Stacking Stapling Tray: 3,000 sheets uns sking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm ( 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3/ SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 lb. bond to 130 lb. cover / 60 to 350 gsm (coc daker-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets at 17	ix 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in./ B5 to coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in./ B5 to A3. tted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x			
Dptional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookk Production Ready Finisher (requires Inte 146mm to 11.7 x 17 <sup>7</sup> /297 x 432mm. Max W 5.75 <sup>*</sup> /148 x 146mm to 13 x 19.2 <sup>*</sup> /330 x 488	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstaplee Proposition staple) 8.5 x 11 in. / A4. Sizes: Stac punch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2 / A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 /eight: 350 gsm. Options: Punch, Inserter an Bmm.	330 x 488 mm (up to 350 gsm) Tray 5: Up to 12 4. Stacking Stapling Tray: 3,000 sheets uns king; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (i 8.5 x 11 in. / A4 unstapled. Stacking Stapling 8/ SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 lb. bond to 130 lb. cover / 60 to 350 gsm (coc 4aker-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets at 17 sheets (90 gsm) uncoated, 35 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sl	ix 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 'in. / B5 to A3. ted and uncoated), sm 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7*/182 x neet top tray, 3,000-sheet stack tray of 5.8			
Dptional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookl Production Ready Finisher (requires Int 146mm to 11.7 x 17"/297 x 432mm. Max W 5.75"/148 x 146mm to 13 x 19.2"/330 x 488 Production Ready Finisher Plus (requires	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ tray: 500-sheets 8.5 x 11 in. / A4 unstaplee e-position staple) 8.5 x 11 in. / A4. Sizes: Stac punch and offset. Paper weights: Top Tray- ed and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2 / A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in./ unch and offset. Paper weights: Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 /eight: 350 gsm. Options: Punch, Inserter an mm. s Interface Decurler Module): Provides sar	330 x 488 mm (up to 350 gsm) Tray 5: Up to 12 1. Stacking Stapling Tray: 3,000 sheets uns- king; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (i 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3/ SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 10. bond to 130 lb. cover / 60 to 350 gsm (coc 4aker-16 lb. bond to 96 lb. cover / 60 to 256 gst ts at 106 to 176 gsm coated or 5 sheets (90 gst) at 106 to 176 gsm coated, 35 sheets (90 gst) d C/Z Folder. Trays: Two output trays, 500-sl me function as the Production Ready Finishe	ix 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 'in. / B5 to A3. ted and uncoated), sm 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7*/182 x neet top tray, 3,000-sheet stack tray of 5.8			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookl Production Ready Finisher (requires Inte 146 mm to 11.7 x 17'/297 x 432mm. Max W 5.75'/148 x 146 mm to 13 x 19.2''/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstaplee position staple) 8.5 x 11 in. / A4. Sizes: Stac punch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2 / A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray- 6 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 /eight: 350 gsm. Options: Punch, Inserter an Bmm. S Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne	(330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 (1) Stacking Stapling Tray: 3,000 sheets uns- king; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm ( 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3/ SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 lb. bond to 130 lb. cover / 60 to 350 gsm (coc daker-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sl me function as the Production Ready Finisher r Finishing Interface Module.	ix 26 in/330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. tited and uncoated), sm 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x seet top tray, 3,000-sheet stack tray of 5.8 or with a 500-sheet top tray and 2,000-sheet			
Dptional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookl Production Ready Finisher (requires Inte 146mm to 11.7 x 17 <sup>7</sup> /297 x 432mm. Max W 5.75 <sup>*</sup> /148 x 146mm to 13 x 19.2 <sup>*</sup> /330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher with Booklet	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstaplece :-position staple) 8.5 x 11 in. / A4. Sizes: Stace pounch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A: / A4. Sizes: Stacking: 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 /eight: 350 gsm. Options: Punch, Inserter an Bm. s Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module): Maker (requires Interface Decurler Module): Contexes and the finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module): Provides sar	(330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 (1) Stacking Stapling Tray: 3,000 sheets uns- sking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm ( 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3/SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 1b. bond to 130 lb. cover / 60 to 350 gsm (coc daker-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets at 17 sheets (90 gsm) uncoated, 35 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sl me function as the Production Ready Finisher r Finishing Interface Module. Jle): Booklet Size: 7.17 x 7.17"/182 x 182mm t	ix 26 in/330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to / coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x heet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she to 13 x 19.2"/330 x 488mm up to 256 gsm.			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookl Production Ready Finisher (requires Inte 146mm to 11.7 x 17'/297 x 432mm. Max W 5.75'/148 x 146mm to 13 x 19.2'/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher with Booklet Trays: 500-sheet top tray, 2,000-sheet stac	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstaplece :-position staple) 8.5 x 11 in. / A4. Sizes: Stace pounch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A: / A4. Sizes: Stacking: 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 /eight: 350 gsm. Options: Punch, Inserter an Bm. s Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module): Maker (requires Interface Decurler Module): Course and Maker (requires Interface Decurler Module): Course and March (requires Interface Decurler Module): Provides sar Maker (requires Interface Decurler Module): Maker (requires Interface Decurler Module): Course Mathematica Maker (requires Interface Decurler Module): Course Mathematica	(330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 (1) Stacking Stapling Tray: 3,000 sheets uns- king; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm ( 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3/ SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 lb. bond to 130 lb. cover / 60 to 350 gsm (coc daker-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sl me function as the Production Ready Finisher r Finishing Interface Module.	ix 26 in/330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to / coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x heet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she to 13 x 19.2"/330 x 488mm up to 256 gsm.			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker I (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookk Production Ready Finisher (requires Inte 146mm to 11.7 x 17'/297 x 432mm. Max W 5.75'/148 x 146mm to 13 x 19.2'/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher with Booklet Trays: 500-sheet top tray; 2,000-sheet stac Offset Catch Tray: 500-sheet stacking.	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ tray: 500-sheets 8.5 x 11 in. / A4. sizes: Stac position staple) 8.5 x 11 in. / A4. Sizes: Stac punch and offset. <b>Paper weights:</b> Top Tray- d and uncoated). <b>Finisher: Offsetting Top Tray:</b> 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A3 / A4. <b>Sizes:</b> Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. <b>Paper weights:</b> Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee <b>erface Decurler Module):</b> Booklet Size: 100 d'ight: 350 gsm. Options: Punch, Inserter an mm. <b>s Interface Decurler Module):</b> Provides sar line finishing options. Includes PFIM Partne <b>Maker (requires Interface Decurler Module</b> ): Karay, saddle-stitch booklet tray (up to 120)	330 x 488 mm (up to 350 gsm) Tray 5: Up to 12 1. Stacking Stapling Tray: 3,000 sheets uns- king; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (i 3.5 x 11 in. / A4 unstapled. Stacking Stapling 8.7 SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 10. bond to 130 lb. cover / 60 to 350 gsm (coc 4aker-16 lb. bond to 96 lb. cover / 60 to 256 gst to 176 gsm coated or 5 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sl me function as the Production Ready Finisher r Finishing Interface Module. Je): Booklet Size: 7.17 x 7.17"/182 x 182mm t pages, 30 sheets/90 gsm uncoated, 15 sheet	ix 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ted and uncoated), im 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x neet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-sheet to 13 x 19.2"/330 x 488mm up to 256 gsm. ts/106 gsm coated).			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookl Production Ready Finisher (requires Int 146mm to 11.7 x 17"/297 x 432mm. Max W 5.75"/148 x 146mm to 13 x 19.2"/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher with Booklet Trays: 500-sheet top tray, 2,000-sheet stacking. Xerox <sup>®</sup> SquareFold <sup>®</sup> Trimmer Module: For	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ tray: 500-sheets 8.5 x 11 in. / A4 unstaplee e-position staple) 8.5 x 11 in. / A4. Sizes: Stac punch and offset. Paper weights: Top Tray- ed and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2 / A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 //eight: 350 gsm. Options: Punch, Inserter an mm. s Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module): tray tx y, saddle-stitch booklet tray (up to 120 ace Trim: 120 pages (30 sheets). Compatibili	(330 x 488 mm (up to 350 gsm) Tray 5: Up to 12 (1. Stacking Stapling Tray: 3,000 sheets uns- king; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (i 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3/ SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 10. bond to 130 lb. cover / 60 to 350 gsm (coc daker-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sl ne function as the Production Ready Finisher r Finishing Interface Module. JB Booklet Size: 7.17 x 7.17'182 x 182mm t pages, 30 sheets/90 gsm uncoated, 15 shee ty: Production Ready Finisher, Booklet Make	ix 26 in/330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to / coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7°/182 x heet top tray, 3,000-sheet stack tray of 5.8 rr with a 500-sheet top tray and 2,000-she to 13 x 19.2°/330 x 488mm up to 256 gsm. ts/106 gsm coated). rr, Crease and Two-Sided Trimmer.			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookle Production Ready Finisher (requires Int 146mm to 11.7 x 17'/297 x 432mm. Max W 5.75'/148 x 146mm to 13 x 19.2''/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher Plus (requires trays: 500-sheet top tray, 2,000-sheet stacking. Xerox® SquareFold® Trimmer Module: For Xerox® C/Z Folder: Sheet Size: 8.5 x 11' (A	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ tray: 500-sheets 8.5 x 11 in. / A4 unstaplee e-position staple) 8.5 x 11 in. / A4. Sizes: Stac punch and offset. Paper weights: Top Tray- ed and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2 / A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 //eight: 350 gsm. Options: Punch, Inserter an mm. s Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module): tray tx y, saddle-stitch booklet tray (up to 120 ace Trim: 120 pages (30 sheets). Compatibili	330 x 488 mm (up to 350 gsm) Tray 5: Up to 12 1. Stacking Stapling Tray: 3,000 sheets uns- king; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (i 3.5 x 11 in. / A4 unstapled. Stacking Stapling 8./ SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 10. bond to 130 lb. cover / 60 to 350 gsm (coc 4aker-16 lb. bond to 96 lb. cover / 60 to 256 gst to 176 gsm coated or 5 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sl me function as the Production Ready Finisher r Finishing Interface Module. Je): Booklet Size: 7.17 x 7.17"/182 x 182mm t pages, 30 sheets/90 gsm uncoated, 15 sheet	ix 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7'/182 x heet top tray, 3,000-sheet stack tray of 5.8 rr with a 500-sheet top tray and 2,000-she to 13 x 19.2'/330 x 488mm up to 256 gsm. ts/106 gsm coated). rr, Crease and Two-Sided Trimmer.			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookl Production Ready Finisher (requires Inte 146mm to 11.7 x 17'/297 x 432mm. Max W 5.75'/148 x 146mm to 13 x 19.2'/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect hird-party in Production Ready Finisher with Booklet Trays: 500-sheet top tray, 2,000-sheet stack Offset Catch Tray: S00-sheet stacking. Xerox <sup>®</sup> SquareFold <sup>®</sup> Trimmer Module: Fc Xerox <sup>®</sup> C/Z Folder: Sheet Size: 8.5 x 11' (A Finisher, Booklet Maker.	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4. sizes: Stac uponth and offset. Paper weights: Top Tray: ed and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2 / A4. Sizes: Stacking: 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 /eight: 350 gsm. Options: Punch, Inserter an Bmm. s Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module): kooklet tray. tray, saddle-stitch booklet tray (up to 120 ace Trim: 120 pages (30 sheets). Compatibili 4). Half-Z Fold Sheet Size: Larger stocks redu	330 x 488 mm (up to 350 gsm) Tray 5: Up to 12 <b>I. Stacking Stapling Tray</b> : 3,000 sheets uns- kking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (o 8.5 x 11 in. / A4 unstapled. <b>Stacking Stapling</b> 3/ SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 lb. bond to 130 lb. cover / 60 to 350 gsm (coc daker-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets at 17 sheets (90 gsm) uncoated, 35 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sl ne function as the Production Ready Finisher r Finishing Interface Module. <b>Je</b> ): Booklet Size: 7.17 x 7.17'/182 x 182mm t pages, 30 sheets/90 gsm uncoated, 15 sheet (cing to 8.5 x 11" (A4). Weight Range: 64 - 90	ix 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. tited and uncoated), sm 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x neet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-she to 13 x 19.2"/330 x 488mm up to 256 gsm. ts/106 gsm coated). er, Crease and Two-Sided Trimmer. gsm. Compatibility: Production Ready			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookl Production Ready Finisher (requires Inte 146mm to 11.7 x 17'/297 x 432mm. Max W 5.75'/148 x 146mm to 13 x 19.2'/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect hird-party in Production Ready Finisher with Booklet Trays: 500-sheet top tray, 2,000-sheet stack Offset Catch Tray: S00-sheet stacking. Xerox <sup>®</sup> SquareFold <sup>®</sup> Trimmer Module: Fc Xerox <sup>®</sup> C/Z Folder: Sheet Size: 8.5 x 11' (A Finisher, Booklet Maker.	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4. sizes: Stac e-position staple) 8.5 x 11 in. / A4. Sizes: Stac up ch and offset. Paper weights: Top Tray: d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2 / A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 // eight: 350 gsm. Options: Punch, Inserter an Bmm. s Interface Decurler Module): Provides sar nline finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module): compatibili (a, tray, saddle-stitch booklet tray (up to 120 ace Trim: 120 pages (30 sheets). Compatibili 4). Half-Z Fold Sheet Size: Larger stocks redu upabilities: Trimming, punching, folding, stag	(330 x 488 mm (up to 350 gsm) Tray 5: Up to 12 (1. Stacking Stapling Tray: 3,000 sheets uns- king; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (i 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3/ SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 10. bond to 130 lb. cover / 60 to 350 gsm (coc daker-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sl ne function as the Production Ready Finisher r Finishing Interface Module. JB Booklet Size: 7.17 x 7.17'182 x 182mm t pages, 30 sheets/90 gsm uncoated, 15 shee ty: Production Ready Finisher, Booklet Make	ix 26 in/330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to , coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. tited and uncoated), sm 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x neet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-she to 13 x 19.2"/330 x 488mm up to 256 gsm. ts/106 gsm coated). er, Crease and Two-Sided Trimmer. gsm. Compatibility: Production Ready			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker I (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookk Production Ready Finisher (requires Inta 146mm to 11.7 x 17"/297 x 432mm. Max W 5.75"/148 x 146mm to 13 x 19.2"/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher with Booklet Trays: 500-sheet top tray; 2,000-sheet stac Offset Catch Tray: 500-sheet stacking. Xerox <sup>®</sup> SquareFold <sup>®</sup> Trimmer Module: Fc Xerox <sup>®</sup> C/Z Folder: Sheet Size: 8.5 x 11" (A Finisher, Booklet Maker.	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4. sizes: Stac position staple) 8.5 x 11 in. / A4. sizes: Stac punch and offset. <b>Paper weights:</b> Top Tray- d and uncoated). <b>Finisher: Offsetting Top Tray:</b> 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A3 / A4. <b>Sizes:</b> Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. <b>Paper weights:</b> Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee <b>erface Decurler Module):</b> Booklet Size: 100 deight: 350 gsm. Options: Punch, Inserter an mm. <b>s Interface Decurler Module):</b> Provides sar line finishing options. Includes PFIM Partne <b>Maker (requires Interface Decurler Module):</b> ck tray, saddle-stitch booklet tray (up to 120 ace Trim: 120 pages (30 sheets). Compatibili 4). Half-Z Fold Sheet Size: Larger stocks redu pabilities: Trimming, punching, folding, stag in Ready Finisher.	330 x 488 mm (up to 350 gsm) Tray 5: Up to 12 <b>I. Stacking Stapling Tray</b> : 3,000 sheets uns- kking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (o 8.5 x 11 in. / A4 unstapled. <b>Stacking Stapling</b> 8.7 SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 1b. bond to 130 lb. cover / 60 to 350 gsm (coc 1aker-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets at 17 sheets (90 gsm) uncoated, 35 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sl ne function as the Production Ready Finisher r Finishing Interface Module. <b>Ja</b> ): Booklet Size: 7.17 x 7.17'/182 x 182mm t pages, 30 sheets/90 gsm uncoated, 15 sheet (cing to 8.5 x 11" (A4). Weight Range: 64 - 90	x 26 in/330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to coated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ted and uncoated), im 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x neet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-sheet to 13 x 19.2"/330 x 488mm up to 256 gsm. ts/106 gsm coated). er, Crease and Two-Sided Trimmer. gsm. Compatibility: Production Ready 48 mm) to 13 x 19.2" (330 x 488 mm). Max			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookl Production Ready Finisher (requires Int 146mm to 11.7 x 17"/297 x 432mm. Max W 5.75"/148 x 146mm to 13 x 19.2"/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher Vise stacking. Xerox® SquareFold® Trimmer Module: Fo Xerox® C/Z Folder: Sheet Size: 8.5 x 11" (A Finisher, Booklet Maker. Xerox® Inserter: Capacity: 250 sheets. Ca Weight: 350 gsm. Compatibility: Productio Xerox® Crase/Two-sided Trimmer: Trim	up to 220 gsm). nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstaplee Position staple) 8.5 x 11 in. / A4. Sizes: Stac punch and offset. Paper weights: Top Tray- ed and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2 / A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 //eight: 350 gsm. Options: Punch, Inserter an mm. s Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module): chroyides that ick tray, saddle-stitch booklet tray (up to 120 ace Trim: 120 pages (30 sheets). Compatibili (4). Half-Z Fold Sheet Size: Larger stocks redu pabilities: Trimming, punching, folding, stap in Ready Finisher. Range: 0.236' (6 mm) to 0.985'' (25 mm). Po	330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 1. Stacking Stapling Tray: 3,000 sheets uns- kking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (i 3. S x 11 in. / A4 unstapled. Stacking Stapling 3. SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 10. bond to 130 lb. cover / 60 to 350 gsm (coc 4aker-16 lb. bond to 96 lb. cover / 60 to 256 gst ta 106 to 176 gsm coated or 5 sheets at 17 sheets (90 gsm) uncoated, 35 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sl me function as the Production Ready Finisher r Finishing Interface Module. ule): Booklet Size: 7.17 x 7.17"/182 x 182mm t pages, 30 sheets/90 gsm uncoated, 15 sheet ity: Production Ready Finisher, Booklet Make (cing to 8.5 x 11" (A4). Weight Range: 64 - 90 bling, stacking. Paper Size: 7.2 x 5.8" (182 x 14)	ix 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to coated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ted and uncoated), m7 to 220 gsm coated). m (coated. Paper Size: 7.2 x 5.7'/182 x heet top tray, 3,000-sheet stack tray of 5.8 rr with a 500-sheet top tray and 2,000-she to 13 x 19.2'/330 x 488mm up to 256 gsm. ts/106 gsm coated). rr, Crease and Two-Sided Trimmer. gsm. Compatibility: Production Ready 48 mm) to 13 x 19.2'' (330 x 488 mm). Max 2'/330 x 488 mm.			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker 1 (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookl Production Ready Finisher (requires Inte 146mm to 11.7 x 17'/297 x 432mm. Max W 5.75'/148 x 146mm to 13 x 19.2'/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher with Booklet Trays: 500-sheet top tray, 2,000-sheet stack Offset Catch Tray: S00-sheet stacking. Xerox <sup>®</sup> C/Z Folder: Sheet Size: 8.5 x 11' (A Finisher, Booklet Maker. Xerox <sup>®</sup> Inserter: Capacity: 250 sheets. Ca Weight: 350 gsm. Compatibility: Production	up to 220 gsm). nd 7:3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4. sizes: Stac position staple) 8.5 x 11 in. / A4. sizes: Stac punch and offset. <b>Paper weights:</b> Top Tray- red and uncoated). <b>Finisher: Offsetting Top Tray:</b> 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2 /A4. Sizes: Stacking: 4 x 6 in. to 12 x 19.2 in. / unch and offset. <b>Paper weights:</b> Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee <b>erface Decurler Module):</b> Booklet Size: 100 /eight: 350 gsm. Options: Punch, Inserter an 8mm. <b>s Interface Decurler Module):</b> Provides sar line finishing options. Includes PFIM Partne <b>Maker (requires Interface Decurler Module):</b> et tray, saddle-stitch booklet tray (up to 120 ace Trim: 120 pages (30 sheets). Compatibili (4). Half-Z Fold Sheet Size: Larger stocks redu upabilities: Trimming, punching, folding, stag in Ready Finisher. Range: 0.236" (6 mm) to 0.985" (25 mm). Pc uction Ready Finisher and Booklet Maker. Bo	(330 x 488 mm (up to 350 gsm) Tray 5: Up to 12 (1. Stacking Stapling Tray: 3,000 sheets uns- kking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (i 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3/ SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 10. bond to 130 lb. cover / 60 to 350 gsm (coc Aaker-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sl ne function as the Production Ready Finisher Finishing Interface Module. ule): Booklet Size: 7.17 x 7.17'182 x 182mm t pages, 30 sheets/90 gsm uncoated, 15 sheet (ing to 8.5 x 11" (A4). Weight Range: 64 - 90 pling, stacking. Paper Size: 7.2 x 5.8" (182 x 14 paper Size: 7.7 x 8.3"/194 x 210 mm to 13 x 19.	ix 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7'/182 x neet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she to 13 x 19.2'/330 x 488mm up to 256 gsm. ts/106 gsm coated). er, Crease and Two-Sided Trimmer. gsm. Compatibility: Production Ready 48 mm) to 13 x 19.2'' (330 x 488 mm). Max 2'/330 x 488 mm. tain or valley creases per sheet.			
Optional Finishing	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (t Two-Tray OHCF: 4000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in., Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookk Production Ready Finisher Plus (requires Inte 146mm to 11.7 x 17'/297 x 432mm. Max W 5.75'/148 x 146mm to 13 x 19.2'/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher with Booklet Trays: 500-sheet top tray, 2,000-sheet stace Offset Catch Tray: 500-sheet stacking. Xerox® SquareFold® Trimmer Module: FC Xerox® Inserter: Capacity: 250 sheets. Ca Weight: 350 gsm. Compatibility: Productio Xerox® Crase/Two-sided Trimmer: Trim Max Weight: 350 gsm. Compatibility: Productio Plockmatic Pro 50/35 Booklet Maker: Bo	up to 220 gsm). nd 7:3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4. sizes: Stac position staple) 8.5 x 11 in. / A4. sizes: Stac punch and offset. <b>Paper weights:</b> Top Tray- red and uncoated). <b>Finisher: Offsetting Top Tray:</b> 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2 /A4. Sizes: Stacking: 4 x 6 in. to 12 x 19.2 in. / unch and offset. <b>Paper weights:</b> Top Tray-16 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee <b>erface Decurler Module):</b> Booklet Size: 100 /eight: 350 gsm. Options: Punch, Inserter an 8mm. <b>s Interface Decurler Module):</b> Provides sar line finishing options. Includes PFIM Partne <b>Maker (requires Interface Decurler Module):</b> et tray, saddle-stitch booklet tray (up to 120 ace Trim: 120 pages (30 sheets). Compatibili (4). Half-Z Fold Sheet Size: Larger stocks redu upabilities: Trimming, punching, folding, stag in Ready Finisher. Range: 0.236" (6 mm) to 0.985" (25 mm). Pc uction Ready Finisher and Booklet Maker. Bo	(330 x 488 mm (up to 350 gsm) Tray 5: Up to 12 (330 x 488 mm (up to 350 gsm) Tray 5: Up to 12 (1) <b>Stacking Stapling Tray</b> : 3,000 sheets uns- kking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St (6 lb. bond to 130 lb. cover / 60 to 350 gsm (o (3,5 x 11 in. / A4 unstapled. <b>Stacking Stapling</b> (3,5 x 3, 11x17 in., 8,5 x 14 in., A3 or A6 to SRA3. Stapling; 7,25 x 10.5 in. to 11 x 17 (lb. bond to 130 lb. cover / 60 to 350 gsm (cod (aker-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sl me function as the Production Ready Finisher r Finishing Interface Module. <b>1</b> (b): Booklet Size: 7.17 x 7.17'/182 x 182mm t pages, 30 sheets/90 gsm uncoated, 15 sheet (cing to 8.5 x 11" (A4). Weight Range: 64 - 90 (ling, stacking. Paper Size: 7.2 x 5.8" (182 x 14 aper Size: 7.7 x 8.3"/194 x 210 mm to 13 x 19. Uffering Unit: Up to five customizable mouni abilities: Face trimming, square fold, rotate of	ix 26 in./330 x 660 mm (up to 220 gsm). tapled or 100 sets (dual or 4-position stag apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to coated and uncoated). Stacker Tray-16 lb. <b>Tray:</b> 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ted and uncoated), mm (coated, Paper Size; 7.2 x 5.7°/182 x neet top tray, 3,000-sheet stack tray of 5.8 rr with a 500-sheet top tray and 2,000-she to 13 x 19.2°/330 x 488mm up to 256 gsm. ts/106 gsm coated). rr, Crease and Two-Sided Trimmer. gsm. Compatibility: Production Ready 48 mm) to 13 x 19.2° (330 x 488 mm). Max 2°/330 x 488 mm. tain or valley creases per sheet.			

Configurations vary by geographical location.

#### For more information, go to **xerox.com/PrimeLink**.

©2020 Xerox Corporation. All rights reserved. Xerox®, PrimeLink®, Smart Kit®, SquareFold® and Xerox Extensible Interface Platform® are trademarks of Xerox Corporation in the United States and/or other countries. The information in this brochure is subject to change without notice. 02/20 PN03829 BR26905 PC9BR-01UC

